

COUNTING SCALE

This economical high resolution counting scale is designed with simplicity in mind. In less than a minute, operators are easily familiar with standard operation. Performance is enhanced by utilizing over 300,000 internal counts and the vibration resistance feature helps the TCS3T to continually make accurate measurements even when used in a disturbed environment.



TCS3T

Standard Features & Benefits:

20 KEY NUMERIC KEYPAD-

The 20 key membrane panel allows entry of numeric data, such as known tare values, APW'S, and specific sample sizes from 1 to 99.999

- **OPERATES FROM RECHARGEABLE BATTERY OR** AC POWER CORD
- **TARGET FUNCTION** (High limit value)
- PRESET TARE (Up to 10 weights)
- STATIC OVERLOAD PROTECTION
- THREE LARGE BACKLIT LCD'S- displays simultaneously show Gross Weight, Unit Weight, and Piece Count

• 1:300,000 INTERNAL RESOLUTION-

High internal resolution provides greater sensitivity, for increased counting accuracy and weighments


ACCUMULATOR FUNCTION-


Can accumulate either pieces or weight, and print total.

- RS 232 PORT- Connect to serial printer
- **VIBRATION RESISTANCE**
- PRESET UNIT WEIGHT (Up to 10 weights)
- **CHARGING INDICATOR**
- LOW BATTERY INDICATOR
- **AUDIBLE FEEDBACK**


Specifications:	Model:	Capacities
Displays: 5-1/2, 7-Segment, 7 annunciators LCD with LED backlight	TCS3T-6 lb	6 lb x 0.0002 l
6-digit, 7 segment, 4 annunciators LCD with LED backlight	TCS3T-12 lb	12 lb x 0.0005
Counting Capacity: 99,999	TCS3T-30 lb	30 lb x 0.001
Weighing Resolution: 1:30,000 (Max)	TCS3T-60 lb	60 lb x 0.002
Units of Measure: lb / kg	Dimensions	S:
Operating Temperature: 32°F to 104°F (0°C to 40°C)	Scale Dimension: 13.5" x 11.8"	
Power Requirements: AC115V, 60 Hz	(343 mm x 300 mm x 99 mm)	
6VDC, 4mAH rechargeable battery included	Platter Dimension: 11" x 9"	
Housing: Ivory ABS	(280 mm x 232 mm)	
Sub Platform: Metal	Packaging Dimension: 15.6" x 1	
Platform: ABS with stainless shroud	(395 mm x 350 mm x 165 mm)	
Feet: Non-Skid Hard Rubber		
Net Weight: 8.85 lb (4.0 kg)		279.6mm [11.01"]
Shipping Weight: 11.1 lb (5.0 kg)		
Battery Life: 150 hrs (continuous)		
Recharge Time: 8 hrs		
Min. Sampling Weight: 1.5 d		
Min. Unit Weight: 0.8 d		231,6mm
		231.6mm

Model:	Capacities:	
TCS3T-6 lb	6 lb x 0.0002 lb (3 kg x 0.0001 kg)	
TCS3T-12 lb	12 lb x 0.0005 lb (6 kg x 0.0002 kg)	
TCS3T-30 lb	30 lb x 0.001 lb (15 kg x 0.0005 kg)	
TCS3T-60 lb	60 lb x 0.002 lb (30 kg x 0.001 kg)	
Dimensions:		
Scale Dimension: 13.5" x 11.8" x 3.9"		
(343 mm x 300 mm x 99 mm)		
Platter Dimension: 11" x 9"		
(280 mm x 232 mm)		
Packaging Dimension: 15.6" x 13.8" x 6.5"		





YOUR AUTHORIZED TRANSCELL DEALER IS:



básculas **Precicell** s.a. de c.v.

Lago Mayrán No. 107 Col. Lagos C.P. 38060 Celaya, Gto., México Tel. (461) 615-3435 www.**basculasprecicell**.com **ventas**@basculasprecicell.com



Warranty: 1 Year Limited Warranty

975 Deerfield Pkwy, Buffalo Grove, IL 60089 Tel (847) 419-9180 Fax (847) 419-1515

(800) 503-9180

www.transcell.net