AX3040 Axle Scale



DIMENSIONS 7 foot steel A 83.60 in (2123.44 mm) E 31.00 in (787.4 mm) F B 90.90 in (2308.86 mm) 32.00 in (812.8 mm) C | 141.25 in (3587.75 mm) | G | 5.63 in (143.0 mm) D 30.00 in (762.00 mm) 12 foot steel A 143.60 in (3647.44 mm) E 31.00 in (787.4 mm) B | 150.90 in (3832.86 mm) | F | 32.00 in (812.8 mm) C | 201.2 in (5111.75 mm) | G | 5.63 in (143.0 mm) D 30.00 in (762.00 mm) 14 foot steel A 167.60 in (4257.04 mm) E 31.00 in (787.4 mm) B 174.90 in (4442.46 mm) F 32.00 in (812.8 mm) C 225.25 in (5721.35 mm) G 5.75 in (146.05 mm) D 30.00 in (762.00 mm) 7 foot aluminum A 83.60 in (2123.44 mm) E 31.00 in (787.4 mm) F B 90.90 in (2308.86 mm) 32.00 in (812.8 mm) C | 141.25 in (3587.75 mm) | G | 5.63 in (143.0 mm) D 30.00 in (762.00 mm)

STANDARD FEATURES

- Sizes: 7ft, 12ft and 14ft lengths
- · Construction: steel or aluminum
- Capacity: 60,000 lb or 80,000 lb
- JB4SS Tuff Seal Signal Trim Junction Box
- · Treaded top plate with four lifting eyes
- 10ft EL146HE Interconnect cable with MS-type connectors to go between weigh pads
- · Contains two load cells per platform
- 50 ft EL147HE cable to connect weigh pad to indicator

Ramps

- 32 in W x 25.25 in L
- · Steel or Aluminum
- · Non Legal for Trade

SPECIFICATIONS

Construction:

Steel or Aluminum

Accuracy:

±3%

End Loading Capacity:

100% full scale at 30,000 lb 75% full scale at 40,000 lb

Warranty:

One-year limited warranty

PART NUMBER/PRICE

PART #	DESCRIPTION	DIMENSIONS	EST. SHIP WEIGHT	PRICE
Steel Construction - Painted Black				
112330	60,000 lb (30,000 lb each)	2.5 ft x 7 ft x 5.63 in	2,567 lb	Consult
111748	80,000 lb (40,000 lb each)	2.5 ft x 12 ft x 5.63 in	4,315 lb	Consult
112328	80,000 lb (40,000 lb each)	2.5 ft x 14 ft x 5.75 in	5,235 lb	Consult
Steel Construction - AX3040 Bundle Package				
153059	60,000 lb (30,000 lb each) includes 920i Universal 115 VAC with short axle program, SURVIVOR® 4 in LaserLight with Stop/Go light, TM U295 and RS-232 cable	2.5 ft x 7 ft x 5.63 in	2,667 lb	Consult
153060	80,000 lb (40,000 lb each) includes 920i Universal 115 VAC with short axle program, SURVIVOR® 4 in LaserLight with Stop/Go light, TM U295 and RS-232 cable	2.5 ft x 12 ft x 5.63 in	4,415 lb	Consult
153061	80,000 lb (40,000 lb each) includes 920i Universal 115 VAC with short axle program, SURVIVOR® 4 in LaserLight with Stop/Go light, TM U295 and RS-232 cable	2.5 ft x 14 ft x 5.75 in	5,335 lb	Consult
Aluminum Construction - Glass Beaded				
112329	60,000 lb (30,000 lb each)	2.5 ft x 7 ft x 5.63 in	1,030 lb	Consult
Aluminum Construction - AX3040 Bundle Package				
153062	60,000 lb (30,000 lb each) includes 920i Universal 115 VAC with short axle program, SURVIVOR® 4 in LaserLight with Stop/Go light, TM U295 and RS-232 cable	2.5 ft x 7 ft x 5.63 in	1,130 lb	Consult





